Revision: 11.05.2020

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2020

Version number 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RC CAR PROTECT
- · UFI: J2GF-TE0G-Y00Y-8MG8
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

See details of exposure scenarios in Annex

Professional use of sprays Industrial use of sprays

Private use of sprays

· Application of the substance / the mixture

Only for proper handling.

Cleaning and maintenance agent

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MW Handel GmbH

Feldweg 3

4040 Linz

Austria

Tel-Nr: +43 732/675500

www.mwrcproducts.com

- · Further information obtainable from: Product safety service
- 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.

STOT SE 3 H336

May cause drowsiness or dizziness.

Asp. Tox. 1 H304

May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light paraffinic isopentane

Camphor oil

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

	(Contd.	of page 1)
H336	May cause drowsiness or dizziness.	
· Precaution	ary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other sources. No smoking.	ignition
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for brea	athing.
P312	Call a POISON CENTER/doctor if you feel unwell.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/	122 °F.
P501	Dispose of contents/container in accordance with local/regional/r international regulations.	national/
22046	a-auda	

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	50-70%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-25%
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-7.5%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents	
aliphatic hydrocarbons	≥30%
perfumes	

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

GB

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Remove residues with soap and water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B

(Contd. on page 4)

Version number 1.0 Revision: 11.05.2020 Printing date 11.05.2020

Trade name: RC CAR PROTECT

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
106-97-8 butane, pure		
WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		

L						
· DNELs	· DNELs					
Hydrocar	bons, C9-C11, n-alkanes, isoalkanes,	cycloalkanes, <2% aromatics				
Oral	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)				
Dermal	DNEL / Workers / Systemic effects / Long-term	300 mg/kg/24h (worker)				
	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)				
Inhalative	DNEL / Workers / Systemic effects / Long-term	1,500 mg/m3 (worker)				
	DNEL/general population/Systemic effects/Long-term	900 mg/m3 (consumer)				
64742-55-	64742-55-8 Distillates (petroleum), hydrotreated light paraffinic					
Dermal	DNEL / Workers / Local Effects / Long-term	1 mg/kg/8h (worker)				
Inhalative	DNEL	2.7-5.4 mg/m3/8h (worker)				
	DNEL	1.2 mg/m3/24h (consumer)				

		-
·PNECs	3	
64742-	55-8 Distillates (petroleum), hydrotre	ated light paraffinic
Oral P	NEC / Predators / Secondary poisoning	9.33 mg/kg food (secondary poisoning
		(predators))

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABĖK.

(Contd. on page 5)

Version number 1.0 Revision: 11.05.2020 Printing date 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 4)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- Body protection: Protective work clothing

SE	CHON 9: Ph	ysıcaı and c	nemicai	properties
· 9.1	Information on	basic physica	l and chen	nical properti

SECTION 9. Physical and chemin	cai properties	
· 9.1 Information on basic physical and chemical properties · General Information · Appearance:		
Form: Colour:	Liquefied gas colourless to light yellow	
· Odour: · Odour threshold:	Solvent-like Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. :: Not applicable, as aerosol.	
· Flash point:	<-10 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	365 °C (DIN 51794)	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	1.5 Vol % 8.5 Vol %	
· Vapour pressure at 20 °C:	2,100 hPa	
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	0.714 g/cm³ (ASTM D 4052) Not determined. Not determined. Not applicable.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	

(Contd. on page 6)

Version number 1.0 Revision: 11.05.2020 Printing date 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 5)

· Viscosity:

Dynamic: Not determined.

<1 mm²/s @ 40 °C (DIN 51562-1) Kinematic: · 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Oral	LD50	5,000-15,000 mg/kg (rat)	
	NOAEL	1,000-5,000 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rat)	
		3,160-5,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)	
	LC50 / 8h	41-4,467 ppm (rat)	
	LC50 / 8h	5 mg/l (rat)	
	NOAEL	200 ppm (rat)	
	NOAEC	275-10,400 mg/m3 (rat)	
106-97-8 I	butane, pure		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	LC50 / 4h	658 mg/l (rat)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.2-21.4 mg/l (rat)	
	LOAEC	21.6 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	
64742-55-	8 Distillates (p	etroleum), hydrotreated light paraffinic	
Oral	LD50	5,000 mg/kg (rat)	
	LOAEL	125 mg/kg/24h (rat)	
Dermal	LD50	2,000-5,000 mg/kg (rabbit)	
	NOAEL	150 mg/kg/24h (mouse)	
(Contd. on			

Version number 1.0 Revision: 11.05.2020 Printing date 11.05.2020

Trade name: RC CAR PROTECT

			(Contd. of page 6
		30-2,000 mg/kg/24h (rat)	, , ,
		1,000 mg/kg/24h (rabbit)	
	LOAEL	100 mg/kg/24h (mouse)	
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)	
	NOEL	220 mg/m3 (rat)	
	NOAEL	980 mg/m3 (rat)	
74-98-6 pi	ropane		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.214-21.394 mg/l (rat)	
	LOAEC	21.64 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	0.131 mg/l/28d (fish)
NOELR	0.23 mg/l/21d (aquatic invertebrates)
	(Conto

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

 	(Contd. of page 7)		
NOELR	3-100 mg/l/72h (algae / cyanobacteria)		
106-97-8	B butane, pure		
LC50	24.1-147.5 mg/l/96h (fish)		
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)		
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)		
64742-5	5-8 Distillates (petroleum), hydrotreated light paraffinic		
LL50	10,000 mg/l/96h (aquatic invertebrates)		
	100 mg/l/96h (fish)		
	>100 mg/l/96h (Pimephales promelas) (OECD 203)		
LL50	10,000 mg/l/72h (aquatic invertebrates)		
LL50	10,000 mg/l/48h (aquatic invertebrates)		
EL50	10,000 mg/l/48h (aquatic invertebrates)		
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)		
74-98-6 propane			
LC50	24.11-147.54 mg/l/96h (fish)		
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)		
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)		
40.00	esistence and design de life. No finishes relevant information available		

• 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)		
106-97-8 butane, pure			
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic			
Partition coefficient	>3.5 [] (log Kow) (Bioaccumulation)		
74-98-6 propane			
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		

- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

(Contd. on page 9)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 8)

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous

substances

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport informati	ion
14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class	2 5F Gases.
Label IMDG, IATA	2.1
Class Label	2.1 2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maxim
Segregation Code	capacity of 1 litre: Category A. I AEROSOLS with a capacity above 1 lit Category B. For WASTE AEROSOL Category C, Clear of living quarters. SG69 For AEROSOLS with a maxim capacity of 1 litre: Segregation as for class 9. Stow "separa

(Contd. on page 10)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

	(Contd. of page
	For AEROSOLS with a capacity above litre:
	Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriat subdivision of class 2.
14.7 Transport in bulk according to And II of Marpol and the IBC Code	nex Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National chemical directories

Components listed or exempted from listing:

TSCA (USA)

DSL/NDSL (CDN)

EINECS/ELINCS/NLP (EU)

ENCS/METI (J)

AICS (Aus)

IECSC (CN)

ECL/KECI (KOR)

PICCS (RP)

- · UFI Code J2GF-TE0G-Y00Y-8MG8
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 10)

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Annex: Exposure scenario 1

- · Short title of the exposure scenario Industrial use of sprays
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.

(Contd. on page 12)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 11)

· Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

- · Short title of the exposure scenario Professional use of sprays
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.

(Contd. on page 13)

Printing date 11.05.2020 Version number 1.0 Revision: 11.05.2020

Trade name: RC CAR PROTECT

(Contd. of page 12)

- · Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of sprays
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · **Technical protective measures** No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · **Disposal measures** Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.